



## Technical Data Sheet

### Pb 9100 – Carpet tape

#### ➤ Description

Double-sided adhesive tape. High-tack and high coating weight adhesive which allows coupling on irregular surfaces. From many surfaces can shows clean peel off.

#### ➤ Carrier

Cotton Cloth

#### ➤ Liner

Siliconised paper Havana 80 g/m<sup>2</sup>

#### ➤ Adhesive

White, solvent natural rubber

Free from plasticizers and heavy metals. Meets RoHs specifications.

#### ➤ Area of use

Designed for carpet and floor covering laying and its attribute permanent bonding of materials with rough or porous surfaces. We assure clean removal without any adhesive residues from many surfaces like concrete, steel, photopolymer cliché, flexo sleeve.

#### ➤ Technical Data

Thickness (AFERA 5006)	380 microns
Temperature resistance	From -10° up to 45 °C Short term: 60°C
Peel Tack AFERA 5001	12 N/25 mm (+-2)
Tensile strength	55 N/cm
Elongation (AFERA 5004)	6 %
Colour	White
Shelf life	12 months, in closed original packing. At temperature of 21°C and a relative humidity of 50%. The quality and durability of the tape may vary according to temperature and humidity. Low temperatures can increase the risk of condensation, consequently reducing the tack of the self-adhesive product

**PROFIBOND Slovakia, s.r.o.**

**Office:** Mlynská 694/2, Stropkov, 091 01

**GSM:** + 421 948 784 464

**mail:** [profibond@profibond.sk](mailto:profibond@profibond.sk)

**web:** [www.profibond.sk](http://www.profibond.sk)